



*The terminal adapter
for a fast connection
using the ISDN basic rate
for EIB systems
with RS232/V.24 bus coupler.*

Functions

- AT command set for transparent building of connections (PC side)
- Automatic building of connections using group addresses (up to 100 addresses)
- Automatic disconnect after configurable time out
- Interface speed: 9600, 19200 (for BCU 2.0) Bit/s
- EIB protocol at RS232/V.24 interface
- Caller identification with configurable access permission
- Cost information in local currency
- Programmable MSN (Multiple Subscriber Number)
- Functionality upgradeable (EPROM)

Features

- Compact case, 164x104x44 mm
- Supports one ISDN B channel (64 kBit/s) and the ISDN D channel (16 kBit/s)
- 256 kB random access memory for I/O buffers
- Specifications I.430 (Layer 1), Q.921 (Layer 2) and Q.931 (Layer 3) implemented
- Approved by: Swisscom Schweizerische PTT: BAKOM 92.1224.I.N
- Approved by: die Deutsche PTT: A105948D
- Further approvals by request
- 1 year warranty including software upgrades

Package Content

- SLink21 EIB ISDN terminal adapter
- 1 ISDN cable and 1 RS232 cable for EIB/
RS232 coupler or switch box for PC
- Power supply
- PDF manual
- Configuration software

Informations

- The software for building connections, the manual and further informations may be found in the internet at <http://www.seal.ch/eib.htm>

